


PRIMARY CORNER DESCRIPTION Special M.C. E-W Center line Sec. 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1728, surveyed May 1994-April 1995 - (DCSO records Vol. 52 Page(s) 19841)

-----  
24.620 chs - (S.89°48'30"W. from E ¼ Sec. 11)  
True point for the special meander cor. on the E & W centerline of sec. 11, at intersection with the adjusted record meanders of the left bank of the Umpqua River. This point falls between the river edge and high water line, on a steep sandy bank, where it is impractical to establish a permanent monument.

26.370 chs  
Point selected for the witness cor. to the special meander cor. on the E & W centerline of sec. 11.  
Set a stainless steel post, 28" long, 2½" diam., 25" in the ground, with brass cap mkd.



from which  
A myrtle, 18" diam., bears S.5°W., 39 lks., mkd. X BT.  
A myrtle, 15" diam. bears N.34 3/4°W., 46½ lks. mkd. X BT.  
Deposit a white "DEEP-1" magnetic marker at the base of the stainless steel post.

BLM Dependent resurvey by Wayne Rogers & A. Bert Skeesick, Cadastral Surveyors & Robert Browning, Surveying Technician, under Group #1878, surveyed May 1998 - Jan. 2000 - (DCSO records Vol. 53 Page(s) 20439-40)

-----  
S.89°47'58"W., on the E. & W. centerline of sec. 11.  
1740.43 (26.370 chs.) The WC to the special meander cor. on the E & W centerline of sec. 11, monumented with a stainless steel post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which bearing trees mkd. by Bedell  
A myrtle, 19" dia., bears S.5°W., 25.7 ft., with healed double blaze.  
A myrtle, 15" dia. bears N.34¾°W., 30.7 ft. with healed double blaze.

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - Aug. 19, 2014 - C.S. File 67/41-51

-----  
BC fd. Ok; 2 BTs as described, re-tagged and flagged as necessary. Compass decl. 15½°E.