

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36; 1 & 2 of T25-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Wm. R. Whipple under Contract #622 dated June 23, 1893 (DCSO records, Volume 8 Page 3227)

Set a post, 4 ft. long, 4" sq., 24" in the ground, marked T24S S36 on NE.; T25S S1 on SE.; R7W S2 on SW.; and S35 on NW faces with 1 notch on E and 5 notches on W edges, from which

- A Fir 24" dia., bears N.16½°E., 60 lks. dist., mkd. T24S R7W S36 BT.
- A Fir 40" dia., bears S.61°E., 114 lks. dist., mkd. T25S R7W S1 BT.
- A Fir 30" dia., bears S.17°W., 124 lks. dist., mkd. T25S R7W S2 BT.
- A Fir 30" dia., bears N.50°W., 103 lks. dist., mkd. T24S R7W S35 BT.

Bureau of Land Management resurvey by Lynn Roseberry under Group #645, Survey, July 1967/Sept. 1968 (DCSO records, Volume 36 Pages 14950-51)

Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of the orig. corner. Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 24 S R 7 W
 S 35 | S 36
 S 2 | S 1
T 25 S R 7 W
 1967

from which

- A Fir 17" dia., bears N.59°E., 13 lks. dist., mkd. T24S R7W S36 BT.
- A Fir 25" dia., bears S.16¼°E., 57 lks. dist., mkd. T25S R7W S1 BT.
- A Fir 17" dia., bears S.29½°W., 31½ lks. dist., mkd. T25S R7W S2 BT.
- A Fir 43" dia., bears N.50½°W., 183 lks. dist., mkd. T24S R7W S35 BT.

Fd. Ok, by Mark Smalley, 10/94 - C.S. File 63/154-18