

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3235-36)

Set a post 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on W. face, from which
A Cedar 24" dia., bears S.47°E., 38 lks. mkd. ¼ S BT.
A Fir 20" dia., bears S.76½°W., 34 lks. mkd. ¼ S BT

Survey by Mark Smalley - For: Roseburg Forest Products - Oct. 1994 - C.S. File 63/154-19

Found - 24" Cedar S.47°E., 25.1 ft. (1893 GLO) now 54" healed.
20" Fir S.76½°W., 22.4 ft. (1893 GLO) now 44", healed.

Set 5/8" x 48" iron rod and alum. cap mkd. T24S R7W

¼
35 | 36
LS 2354
1994

New BTs- 7" W.Fir N.19°W., 4.1 ft. scribed ¼ S BT.
11" Fir N.80°E., 11.9 ft. scribed ¼ S BT.