

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCS0 records Vol. 8 Page(s) 3236)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 25, 26, 35 and 36, marked T24S S25 on NE.; R7W S36 on SE.; S35 on SW.; and S26 on NW. faces with 1 notch on S. and E. edges, from which
A Fir 14" dia., bears N.54°E., 64 lks. dist. mkd. T24S R7W S25 BT.
A Fir 20" dia., bears S.6°E., 58 lks. dist. mkd. T24S R7W S36 BT.
A Fir 20" dia., bears S.48½°W., 61 lks. dist. mkd. T24S R7W S35 BT.
A Fir 30" dia., bears N.61½°W., 35 lks. dist. mkd. T24S R7W S26 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Aug. 4, 1958 - C.S. File 49/41-18

Found - Old scribed stake at corner.
Orig. 14" now 22" Fir stump, shows good scar at top of cut, N.54°E., 42.2 ft.
Orig. 30" now 40" Fir snag, I open and find good scribing, "W", N.61½°W., 23.1 ft.
Orig. 20" now 36" Fir, shows good scar. I do not open, S.48½°W., 40.3 ft.
No trace of original SE. BT.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 7 W
S 26 | S 25
S 35 | S 36
1958

New BTs- 12" R.Fir bears S.88½°E., 16.5 ft. scribed S36 T24S R7W CS BT.
18" W.Fir bears N.16°E., 32.9 ft. scribed S25 T24S R7W CS BT.
6" Cedar bears N.9½°W., 51.7 ft. scribed S26 CS BT.
Orig. SW. BT, now alive. I do not rescribe.

1958 brass cap and original BTs. All 1958 CS BTs were destroyed by logging. - May 1982 by Les Roberts - M 92-36

Survey by Mark Smalley - For: Kenneth Ford - Oct. 1994 - M 121-7

Found - 1958 DCS0 brass cap and 3 ft. tall rebar with metal tag "PLS 1039". (Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New BTs-	40" Fir N.61½°W., 23.1 ft., snag. OBT.
	14" Fir N.54°E., 42.2 ft., stump. OBT.
	36" Fir S.48½°W., 40.3 ft., healed. OBT.
	10" Fir N.55°W., 35.3 ft. scribed "S 36 BT"
	10" Fir N.32°E., 15.6 ft. scribed "S 25 BT"
	12" Fir S.2°E., 18.4 ft. scribed "S 36 BT"
	10" Fir S.47°W., 16.1 ft. scribed "S 35 BT"