

PRIMARY CORNER DESCRIPTION Sec Cor for 23, 24, 25 and 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3239)

Set a post 4 ft. long, 4' sq., 24" in the ground for cor. to secs. 23, 24, 25 and 26, marked T24S S24 on NE.; R7W S25 on SE.; S26 on SW.; and S23 on NW. faces, with 1 notch on E. and 2 notches on S. edges, from which
A W.Fir 30" dia., bears N.4°E., 49 lks. dist. mkd. T24S R7W S24 BT.
A Cedar 24" dia., bears S.62°E., 88 lks. dist. mkd. T24S R7W S25 BT.
A Cedar 24" dia., bears S.79°W., 97 lks. dist. mkd. T24S R7W S26 BT.
A Cedar 10" dia., bears N.40°W., 30 lks. dist. mkd. T24S R7W S23 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - Aug. 4, 1958 - C.S. File 49/41-20

Found - Orig. 24" now 32" Cedar, bears S.79°W., 64.0 ft. Open face, shows good scribing.
Orig. 24" now 40" Cedar, bears S.62°E., 58.1 ft. Shows good scar. I do not open.
Orig. 30" now 32" W.Fir, N.4°E., 32.3 ft. Shows good scar. I do not open.
No trace of orig. NW. BT found.
Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 7 W
S 23 | S 24
S 26 | S 25
1958

New BTs- 8" R.Fir bears N.19°W., 4.2 ft. scribed S23 T24S R7W CS BT.
The orig. N.4°E., 32.3 ft., now 32" is OK. I do not rescribe.
14" R.Fir bears S.42°W., 9.7 ft. scribed S26 T24S R7W CS BT.
The orig. S.62°E., 58.1 ft., now 40", is OK. I do not rescribe.

BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 807 Surveyed June/July. 1973 (DCSO records Vol. 37 Page(s) 15289)

The Sec. cor., perpetuated by Byron in 1958, monumented with an iron post, 1½" dia., firmly set, protruding 14" above (Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 600300

PRIMARY CORNER DESCRIPTION Sec Cor for 23, 24, 25 and 26

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

ground with brass cap mkd. in 1958, from which the remains of the original bearing trees:
A root hole bears N.4°E., 49 lks. dist. with a down Fir alongside 32" dia., with healed blaze.
A Cedar 40" dia., bears S.62°E., 88 lks. dist. with healed blaze.
A Cedar 32" dia., bears S.79°W., 97 lks. dist. with healed blaze.
and bearing trees mkd. by Byron:
A Fir 16" dia., bears S.42°W., 14 lks. dist., with healed blaze.
A Fir 10" dia., bears N.17°W., 6½ lks. dist., with healed blaze.
and a new bearing tree;
A Fir 10" dia., bears N.29½°E., 26 lks. dist. mkd. T24S R7W S24 BT.

Fd. Ok by Ronald Quimby, 2/2001 - C.S. File 65/36-4

Douglas Co. Surveyors Office - Crew: Stephen Flauser & Jeff Lorsung- 12/9/2019 (filed 11/3/2022) - C.S. File 67/54-33

Reported as Fd OK
1 BT (S.42°W.) fallen
1 BT (S.79°W.) Now solid 6' tall stump