

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3241-42)

-----  
Set a stone 12x8x6 ins., 8" in the ground for 1/4 sec. cor., marked 1/4 on W. face, from which  
A Fir 40" dia., bears N.49°E., 49 lks. dist. mkd. 1/4 S BT  
A Fir 6" dia., bears N.19°W., 39 lks. dist. mkd. 1/4 S BT

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - June 1958 - C.S. File 49/4110

-----  
Found - Stone at corner as recorded.  
Orig. 40" now 44" stump, N.49°E., 32.3 ft. I open old scar and find good scribing "BT"  
Orig. 6" now 16" Fir, N.19°W., 25.7 ft., alive, shows old scar. I do not open.  
Set brass cap alongside corner stone, mkd.  
County Surveyors Office  
T 24 S R 7  
1/4 S23 | S24  
1958  
New BT - 9" Cedar bears S.86°E., 10.2 ft. scribed 1/4 S24 CS BT

Fd. OK, April 1994 by L. Dolan - M 121-64  
Fd. OK, Oct. 1995 by D. Bentz - M 123-6  
Fd. ok by D. Edwards 7/2007 - M153-56