

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73 dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3197-8)

Set post, cor. secs. 11, 12, 13, & 14, from which
 A Fir, 50" dia., bears S.89°E., 1222 lks.
 A Fir, 6" dia., bears S.78°W., 62 lks.
 A Maple, 6" dia., bears N.48°W., 42 lks.
 No tree convenient NE of cor.

BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1728, surveyed May 1994-April 1995 - (DCSO records Vol. 52 Page(s) 19830-1)

Point for the cor. of secs. 11, 12, 13, & 14, at proportionate distance; there is no remaining evidence of the original corner.

Set a stainless steel post, 28" long, 2½" diam., 22" in the ground, with brass cap mkd. T24S R7W
 _____ S 11|S 12
 S 14|S 13
 1994

from which
 A stainless steel post, 28" long, 2½" diam., set 22" in the ground, for a reference monument, bears N.49°48'00" E., 32 lks., with brass cap mkd. RM T24S R7W S12 21.1 FT TO COR 1994 and an arrow pointing to the corner. Deposit a silver "DEEP-1" magnetic marker at the base and a steel fence post, 6 ft. long, alongside the stainless steel post.
 A stainless steel post, 28" long, 2½" diam., set 22" in the ground, for a reference monument, bears S.50°29'00"E., 67 lks., with brass cap mkd. RM T24S R7W S13 44.2 FT TO COR 1994 and an arrow pointing to the corner. Deposit a purple "DEEP-1" magnetic marker at the base and a steel fence post, 6 ft. long, alongside the stainless steel post.
 Deposit a white "DEEP-1" magnetic marker at the base and a steel fence post, 6 ft. long, alongside the corner post.
 The corner is located West, 5.65 chs. from State Highway No. 138, asphalt surface, 40 lks. wide, bears N.20°W. and S.20°E. From this point, the BLM Geodetic Control Station No. EC 41229, at latitude 43° 30' 04.567" N., longitude 123° 29' 29.393" W. (NAD 1927), determined by the NAVSTAR Global Positioning System, bears N.23°14'52"W., 63.045 chs. (mean bearing and sea level distance); monumented with an aluminum cap, 3¼" diam., set flush in bedrock, in concrete, mkd. EC 41229 GPS 1994 and a triangle.

Found OK by C. Sweeden, April 2004 - 2004-0023