

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3198)

Set ¼ sec. post, from which
 An Oak 12" dia., bears N.15°E., 15 lks. dist.
 An Oak 12" dia., bears N.35°W., 19 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Ray Irving, Chainman - July 20, 1954 - C.S. File 46/24

Found - Mound of stone and 14" x 10" x 18" rock with cross on top, checks bearing and distance to 12" Oak stump scribed BT which is probably orig. BT. This corner has been renewed about 20 years ago.

 We found and cut 28" W.Oak scribed "CS ¼ S12," N.19°E., 27.5 ft. Tree alive and in good condition.

 Also a 20" W.Oak, N.80½°W., 16.6 ft., blazed. We did not cut out. Tree in good condition.

Set a 1" x 30" Iron pipe with brass cap at side of rock with cross, marked: County Surveyors Office 1954 ¼ cor. 11 12 T24S R7W.

Blazed and scribed:

 A 16" W.Oak N.2°W., 35.2 ft. mkd. "¼ S11 CS BT".

Fd. & used on BLM Dependent resurvey by Dale Bedell, Cadastral Surveyor, under Group #1728, surveyed May 1994-April 1995 - (DCSO records Vol. 52 Page(s) 19840-1)

Fd. & used on BLM Dependent resurvey by Wayne Rogers & A. Bert Skeesick, Cadastral Surveyors & Robert Browning, Surveying Technician, under Group #1878, surveyed May 1998 - Jan. 2000 - (DCSO records Vol. 53 Page(s) 20438-9)