

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 602400

PRIMARY CORNER DESCRIPTION CC for Secs. 23 & 24 only (North)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3241)

-----  
(Intersect E. and W. section line, 126 lks. E. of cor. to secs. 13, 14, 23 and 24, which cor. will be described in the notes of the resurvey of the line bet. secs. 13 and 14.)  
At the point of intersection, I set a sandstone 16x12x3 ins., 12" in the ground for closing cor. to secs. 23 and 24, marked CC with 3 notches on S. and 1 notch on E. edges, from which  
A Cedar 24" dia., bears S.78°E., 77 lks. dist. mkd. T24S R7W S24 BT.  
A Fir 36" dia., bears S.39°W., 27 lks. dist. mkd. T24S R7W S23 BT.  
A Fir 50" dia., bears N.80°E., 34 lks. dist. mkd. T24S R7W CC S23 and 24 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - M. Godfrey and S. Bilow, crew - June 3, 1958 - C.S. File 49/41-9

-----  
I find closing cor. for 23 and 24. Find stone marked as recorded at corner. Also 1" steel shaft alongside stone and all BTs as recorded, except SE. BT which is now snag only. The SW. and NE. BTs show good scribing. I do not renew this corner.

Douglas Co. Surveyors Office - Milo E. Godfrey and crew - Jan. 13, 1964 - C.S. File 49/41-54

-----  
Found - 1" steel shaft alongside rock at corner, buried in mud from roots of uprooted BT.  
50" Fir N.80°E., 22.4 ft. scribing still visible in open scar, nearly all pitched over.  
The 36" Fir S.39°W., 17.8 ft. is uprooted and down.  
New BT - 20" D.Fir S.20°W., 41.8 ft. mkd. T24S R7W CC S23 CS BT.

BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 807 Surveyed June/July. 1973 - (DCSO records Vol. 37 Page(s) 15288)

-----  
The original closing cor. of secs. 23 and 24, on the S. bdy. of sec. 13, perpetuated by Godfrey in 1964, monumented with an iron pipe, 1" dia., firmly set, protruding 8" above ground, from which the remains of the original bearing trees:  
A Fir 50" dia., bears N.80°E., 34 lks. dist., with scribe marks BT visible on opened blaze.  
(Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 602400

PRIMARY CORNER DESCRIPTION CC for Secs. 23 & 24 only (North)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

A root hole bears S.39°W., 27 lks. dist., with a down Fir alongside, size indeterminate, no marks visible. and a bearing tree mkd. by Godfrey

A Fir 22" dia., bears S.27°W., 62½ lks. dist., with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

S 13  
S 23 | S 24  
T 24 S R 7 W  
C C  
1973

from which a new bearing tree

A Fir 6" dia., bears S.13°E., 42½ lks. dist. mkd. T24S R7W S24 CC BT.

Fd. OK April 1994 by L. Dolan - M 121-64

Fd. OK Oct. 1995 by D. Bentz - M 123-6

-----  
Found Ok by Douglas Co. Surveyors Office - Randall W. Smith & Stephen J. Flause - 2/16/1998 - C.S. File 64/79-9