

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 611400

PRIMARY CORNER DESCRIPTION M.C. on South bdy. Sec. 13

Alias 867560 Description M.C. on right bank, Umpqua River  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #73, dated June 8, 1857 - (DCSO records Vol. 8 Page(s) 3196)

-----  
Mark Myrtle 10" dia., for meander post, from which  
    An Alder 12" dia., bears S.10°E., 19 lks. dist.  
    An Alder 12" dia., bears S.70°E., 24 lks. dist.  
No good trees as convenient on W. side of line.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3268)

-----  
Find no trace of meander cor.

BLM resurvey by Daniel Berry and Charles Akin Cadastral Surveyors, under Group # 807 Surveyed June/July. 1973 (DCSO records Vol. 37 Page(s) 15287-88)

-----  
(29.23 chains)  
Point for the original meander cor., on right bank of Umpqua River, at proportionate distance; there is no remaining evidence of the original corner. This point falls on eroding right bank of River, course S.75°E., where it is impracticable to establish a permanent monument.

(30.03 chains)  
Point for the witness meander cor.  
Set an iron post 28" long, 2½" dia., 26" in the ground with brass cap mkd:

                                  W C  
                                  T 23 S \  
                                  S 13   \  
-----> S 24   \  
                                  R 7 W  
                                  1973

from which  
    A triple Myrtle 23" dia., bears S.2°W., 40 lks. dist. mkd.  
    X BT.  
    No suitable tree available within limits in sec. 13.

Fd. OK, March 1994 by R. Brown - M 118-42

Douglas Co. Surveyors Office - Stephen J. Flause - Mike Koch - July 28, 2014 - C.S. File 67/41-33

-----  
Found - A 3¼" brass cap (properly mkd) on a 2" I.D. iron pipe is set plumb and flush with ground. 1973 BLM  
    No Evidence from orig. survey  
continued next page

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 611400

PRIMARY CORNER DESCRIPTION M.C. on South bdy. Sec. 13

Alias 867560 Description M.C. on right bank, Umpqua River  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

- 1973 - A green and white painted steel fence post of unknown origin; bears S.43°W., 0.8 ft. (This post is removed when bearings are checked, and the replaced in its original location)
- 1973 - A triple myrtle 23" dia., now a 35" dia., myrtle (3 trunks now fused into one trunk to a height of 6+ ft.) shows a fully healed high-low blaze. This tree bears S.2°W., 26.4 ft. (as per record)
- New - A double trunk B.Walnut with a 5" dia., southerly trunk scribed "X" "BT" on a high-low blaze; bears S.69¼°E., 28.8 ft.
- A 5/8" iron rod with a red plastic David Edwards Surveying cap marked in part "LS2339"; bears S.82¼°W., 182.0 ft., agrees with computed meas. from DCSO map file M118-42 (R.Brown) when this property corner was first established.
- A 72" dia., coast redwood which is not blazed or scribed (but is tagged); bears S.34¼°W. 78.8 ft. A group of 4 smaller redwoods growing close together is N.80°W., approx. 27 ft from the 72" BT
- Note - Monument is on flood plain. Shelf-land in and alder and myrtle woods.  
Monument is 50 ft. south of Umpqua River high-bank.  
Compass decl. 15½°E.