

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 640100

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 36; & 1 of T. 25-7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Wm. R. Whipple, under Contract #622 dated June 23, 1893 (DCSO records, Volume 8 Page 3227)

Set a post, 3 ft. long 3" sq., 24" in the ground for 1/4 sec. cor., marked 1/4 S on N. face, from which

A Maple 14" dia., bears S.9°W., 33 lks. dist. mkd.
1/4 S BT.

A Fir 24" dia., bears N.47°E., 33 lks. dist., mkd.
1/4 S BT.

Bureau of Land Management resurvey by Lynn Roseberry, Group #645. Survey, July, 1967/Sept. 1968 (DCSO records, Volume 36 Page 14951)

Point for the 1/4 sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the orig. corner. Set a Iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd:

T 24 S R 7 W
1/4 S 36
S 1
T 25 S
1967

from which

A Cedar 25" dia., bears N.59°W., 62 1/2 lks. dist.,
mkd. 1/4 S36 BT.

A Fir 22" dia., bears S.84°E., 57 1/2 lks. dist.,
mkd. 1/4 S1 BT.

Mark Smalley, L.S. #2354 - For: Roseburg Forest Products - Oct. 1994 - C.S. File 63/154-20

Found - 1967 BLM Brass Cap & I.P.
25" Cedar, N.59°W., 41.3', healed, now 30" (1967 BLM)

New BTs- 22" Fir, S.84°E., 38.0', healed, now 24" (1967 BLM)
7" Fir, N.64°E., 7.8', scribed "1/4 BT"
8" Fir, S.38°W., 20.7', scribed "1/4 BT"