

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3237)

Set a post, 3 ft. long, 3" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face, from which
A Cedar 24' dia., bears N.25°E., 22 lks. dist. mkd. ¼ S BT
A Cedar 24" dia., bears S.70½°E, 78 lks. dist. mkd. ¼ S BT

Survey by Mark Smalley - For: Kenneth Ford - Oct. 1994 - M 121-7

Set 5/8" x 48" Iron rod and alum. cap mkd. "LS 2354", from which
30" Fir N.8°W., 33.0 ft. "¼ S BT"
32" Fir N.56°E., 11.5 ft. "¼ S BT"
10" Cedar S.58°E., 18.7 ft. "¼ S BT"
30" Fir S.64°W, 7.6 ft. "¼ S BT"