

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 8 Page(s) 3240)

Set a post 3 ft. long, 3" sq., 24" in the ground for 1/4 sec. cor., marked 1/4 S on N. face, from which
A Fir 10" dia., bears N.20°E., 34 lks. dist. mkd. 1/4 S BT
A Cedar 30" dia., bears S.47°W., 74 lks. dist. mkd. 1/4 S BT

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - June 1958 - C.S. File 49/41-11

Found - Orig. 30" now 38" Cedar, S.47°W., 48.8 ft., open face, good scribing visible "1/4S".

Orig. NE. BT gone, old cat road here.

Set Brass cap at cor. mkd: County Surveyors Office
T 24 S R 7 W

1/4 $\frac{S\ 24}{S\ 25}$
1958

New BTs- 10" R.Fir bears N.35°W., 15.5 ft. scribed 1/4 S24 CS BT.

The original SW. BT OK.

Fd. OK, April 1994 by L. Dolan - M 121-64

Fd. OK, Oct. 1995 by D. Bentz - M 123-6