

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36, (SE Tsp. Cor.)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Wm. Whipple, under Contract #622 dated June 23, 1893 (DCSO records, Volume 8 Page 3226) and Page 3275)

Intersected East bdy. of Tsp (T24-7) 2.01 chs. N. of the cor. to Tps. 24 & 25 Rgs. 6 & 7.
At point of intersection, I set a post, 4½ ft. long, 4" sq., 24" in the ground for closing corner to Tps. 24 and 25 R 7 W, marked: C C R 7 W on W.; T24S S36 on N.; T25S S1 on S.; with 6 notches on N S and W. faces, from which
A Fir 40" dia., bears N.49°W., 56 lks. dist., mkd.
T24S R7W S36 BT.
A Fir 20" dia., bears S.59½°W., 65 lks. dist., mkd.
T25S R7W S1 BT.
A Fir 40" dia., bears S.4°E., 45 lks. dist., mkd.
CC T24 and 25 S R 7 W BT.

Doug. County Surveyors Office - Milo Godfrey, Deputy; Vernon Tracy; Mike Stone - July 1963 - C.S. File 49/123-87

Found - 50" D.Fir S.59½°W., 42.9 ft., old bark scribing visible, faces corner.
60" D.Fir N.49°W., 37.0 ft. bark shows evidence of having been flattened off with axe. Bark badly burned & no scribe marks found.
Did not find SE tree called for in notes.
Rotten Fir snag S.10°W., 14.3 ft. with portion of old face showing fragments of scribe marks. At some time it was faced off, tree would have been 12" to 15" dia., face & scribing faces approx. N.40°W., not toward corner as set from 2 BTs.
Set Brass cap at cor. mkd: County Surveyors T24S S 36 |
R7W R6W CC
T25S S 1 |
New BTs - 13" D.Fir N.30°W., 111.0 ft. mkd. T24S R7W CC S36
CS BT.
28" I.Cedar N.31°E., 99.2 ft. mkd. CC T24S & 25S R7W
CS BT.
No trees available to SW except old, over ripe & half-dead D.Firs. Did not mark SW tree.
Corner lies approx. 10 ft. West of logging road, nearly at south end of road.

(Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 700100

PRIMARY CORNER DESCRIPTION SE Cor. Sec. 36, (SE Tsp. Cor)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Bureau of Land Management resurvey, by Lynn Roseberry, under Group #645 - Survey, July 1967/Sept. 1968 (DCS0 records, Volume 36 Pages 14951/52)

True point for the closing cor. of Tps. 24 and 25 S., R.7W. Set a Iron post, 28 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd:

T 24 S		T 24 S
R 7 W		R 6 W
CC S 36		S 31
S 1		
T 25 S		
1967		

from which

A Fir 50" dia., bears S.62 3/4°W., 104 lks. dist., mkd. T25S R7W S1 CC BT.

A Fir 60" dia., bears N.42¼°W., 191 lks. dist., mkd. T24S R7W S36 CC BT.

(From this point, the cor. of Tps. 24 and 25 S., R.6W., bears S.0°19'W., 0.17 chs. dist., described in the field notes of a dependent resurvey in T.24S, R6W under this group.)

(From this same point, the orig. closing cor. of Tps. 24 and 25 S., R7W., bears S.89°25'E., 3.65 chs., perpetuated and recorded by the County Surveyor in 1963) (See Point ID #700677)

Fd. Ok by Mark Smalley, Oct. 1994 - C.S. File 63/154-17