

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 700139

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. Sec. 31 only, T24-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3130)

-----  
Set ¼ sec. post, from which  
A Fir 12" dia., bears S.87°E., 44 ks. dist.  
A Fir 8" dia., bears S.3°W., 59 lks. dist.

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #645 Surveyed, Aug/Sept. 1967 - (DCSO records Vol. 36 Page(s) 14942)

-----  
Point for the ¼ sec. cor. of sec. 31 only, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

T 24 S  
S 31  
1/4 R 6 W  
1967

from which

A Fir 8" dia., bears N.1½°E., 217 lks. dist., mkd. ¼ S31 BT.  
A Fir 6" dia., bears S.50½°E., 22 lks. dist., mkd. ¼ S31 BT.

Survey by Mark Smalley - For: Roseburg Forest Products - Oct. 1994 - C.S. File 63/154

-----  
Found - 1967 BLM brass cap.

8" Fir N.1½°E., 143.2 ft. now healed 12" Fir.

6" Fir S.50½°E., 14.5 ft. now healed 14" Fir.

New BTs - 6" Fir N.26°E., 15.3 ft. "¼ S BT" scribed.

11" Fir S.67°W., 15.3 ft. "¼ S BT" scribed.