

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 700140

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. Sec. 36 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #645 Surveyed, Aug/Sept. 1967 - (DCSO records Vol. 36 Page(s) 14942)

Point for the ¼ sec. cor. of sec. 36 only, on the E. bdy. of T24S R7W at midpoint latitudinally.

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap marked:

T 24 S
1/4 S 36
R 7 W
1967

from which

A Fir 6" dia., bears S.23°W., 63 lks. dist., mkd. ¼ S36 BT

A Fir 32" dia., bears N.69°W., 20 lks. dist. mkd. ¼ S36 BT

Corner falls in head of ravine, drains E.

Survey by Mark Smalley, L.S. #2354 - For: Roseburg Forest Products - Oct. 1994 -C.S. File 63/154-21

Found - 1967 BLM Brass Cap & I.P.

32" Fir, N.69°W., 13.2 ft., by 1967 BLM survey, now healed 42" Fir.

6" Fir, S.23°W., 41.6 ft., by 1967 BLM survey, now healed 16" pistol butted Fir.

New BTs- 7" Fir, S.3°E., 26.4 ft., scribed "¼ S BT"

8" Fir, S.76°E., 18.9 ft., scribed "¼ S BT"