

PRIMARY CORNER DESCRIPTION CC for Secs. 25 & 36 only, (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 page(s) 3237) (and Page 3275)

I set a post, 4 ft. long, 4" sq., 24" in the ground for closing cor. to secs. 25 and 36 mkd. C C T24S R7W on W.; S25 on N. and S.36 on S. with 5 notches on N. and 1 notch on S. faces, from which

A Cedar 10" dia., bears N.68½°W., 39 lks. dist., mkd. T24S R7W S25 BT.

A Fir 36" dia., bears S.28°W., 19 lks. dist., mkd. T24S R7W S36 BT.

A Fir 36" dia., bears S.40°E., 35 lks. dist. mkd. T24S R7W C C S25 and 36 BT.

(After setting C C for secs. 25 and 36, I destroyed all marks referring to these sections on old corner.)

BLM Resurvey by Lynn M. Roseberry, Cadastral Surveyor - Under Group #645 Surveyed, Aug/Sept. 1967 - (DCSO records Vol. 36 Page(s) 14943)

The original closing cor. of secs. 25 and 36, determined at record bearing and distance from the original bearing trees;

A Fir stump 40" dia., bears S.40°E., 35 lks. dist., with no marks remaining.

A root hole bears S.28°W., 19 lks. dist., with an uprooted Fir 40" dia., alongside, with no marks visible on burned out blaze.

A Cedar 24" dia., bears N.68½°W., 39 lks. dist., with a healed blaze.

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, with brass cap mkd:

	T 24 S T 24 S
	R 7 W R 6 W
	S 25
CC	----- S 30
	S 36
	1967

from which a new bearing tree

A Fir 38" dia., bears S.43¼°W., 98 lks. dist., mkd. T24S R7W S36 CC BT.

Survey by Mark Smalley, L.S. #2354 - For: Kenneth Ford - Oct. 1994 - M 121-7

Found - 1967 BLM B.C. & I.P.

24" Cedar N.68½°W., 25.7 ft., stump OBT

(Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION CC for Secs. 25 & 36 only, (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

36" Fir, S.40°E., 23.1 ft., stump OBT
36" Fir, S.28°W., 12.5 ft., uprooted OBT
42" Fir, S.43¼W., 64.7 ft., healed
New BTs- 6" Fir, N.41°E., 2.9 ft., scribed "S 30 BT"
9" Fir, S.44°E., 9.0 ft., scribed "S 30 BT"
10" Fir, S.70°W., 19.3 ft., scribed "S 36 BT"