

PRIMARY CORNER DESCRIPTION Cor. Secs. 19 & 30 only, W. Bdy, T24-6

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3129)

- 
- Set post cor. to secs. 19, 30, 24 and 25, from which
- A Fir 11" dia., bears N.87°E., 8 lks. dist.
  - A Fir 12" dia., bears S.46°E., 50 lks. dist.
  - A Fir 12" dia., bears S.66°W., 22 lks. dist.
  - A Fir 20" dia., bears N.63°W., 49 lks. dist.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3161-62)

- 
- The cor. to secs. 19, 30, 24 and 25, the Post being gone, I reestablish same by setting a Cedar post, 4 ft. long, 4' sq., 24" in ground, mkd. T24S S19 on NE.; R6W S30 on SE., R7W S25 on SW.; and S24 on NW. faces with 2 notches on the South and 6 notches on the East edges, from which
- A Fir 11" dia., bears N.87°E., 8 lks. dist. mkd. T24S R6W S19 BT.
  - A Fir 12" dia., bears S.46°E., 50 lks. dist. mkd. T24S R6W S30 BT.
  - A Fir 12" dia., bears S.66°W., 22 lks. dist. mkd. T24S R7W S25 BT.
  - A Fir 20" dia., bears N.63°W., 49 lks. dist. mkd. T24S R7W S24 BT.

Survey by Clifford M. Bryden - Feb. 1956 - C.S. File 42/157

- 
- Location for corner determined by proportional measurement. Set a 4' x 4" Fir post at corner point, from which
- 16" D.Fir bears S.41°20'W., 43.6 ft.
  - 5" D.Fir bears N.64°00'E., 24.5 ft.
  - 24" D.Fir bears S.16°00'E., 36.0 ft.
  - 24" D.Fir bears S.29°50'E., 45.3 ft.
- (Each BT marked RE 3937 BT)

*Note: Above corner reported not common. Per James Byron, above corner bears N.84½°W., 48.9 ft. the BLM brass cap set in next entry.*

BLM dependent resurvey by Joseph S. Gawron under Group #464 surveyed May/June 1962 (DCSO records Vol. 31 Page(s) 13114-15)

-----

(Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 700279

PRIMARY CORNER DESCRIPTION Cor. Secs. 19 & 30 only, W. Bdy., T24-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The cor. of secs. 19 and 30 only, on the W. bdy. of The Tp., (T24S R6W) is determined from the only remaining original bearing tree:

A Fir 52" dia., bears N.63°W., 49 lks. mkd. T24S R7W BT.

At the corner point

Set an iron post, 30" long, 2½" dia., 28" in the ground, with brass cap mkd:

T 24 S  
R 7 W R 6 W  
S 25 S 19  
S 30  
1962

from which

A Fir 10" dia., N.45°E., 83 lks. mkd. T24S R6W S19 BT

A Fir 6" dia., bears S.55°E., 94 lks. dist. mkd. T24S R6W S30 BT.