

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T24-6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors, under Contract #31 dated April 7, 1853 (DCSO records Vol. 8 Page(s) 3127-28)

Set post cor. to secs. 7, 12, 13 and 18, from which
A Laurel 12" dia., bears S.76°W., 35 lks. dist.
A Laurel 8" dia., bears N.25°W., 22 lks. dist.
A Fir 8" dia., bears N.86°E., 35 lks. dist.
A Laurel 12" dia., bears S.72°E., 23 lks. dist.

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #577, dated July 18, 1891 (DCSO records Vol. 8 Page(s) 3185-86)

The cor. to 7, 12, 13 and 18, Post gone. Set a Cedar post, 4 ft. long, 4" sq., 24" in the ground for corner, mkd. T24S S7 on NE.; R6W S18 on SE.; R7W S13 on SW.; and S12 on NW. faces, with 4 notches on the S. and 6 notches on the E. edges, from which
A Fir 8" dia., bears N.86°E., 35 lks. dist., mkd. T24S R6W S7 BT.
A Laurel 12" dia., bears S.72°E., 23 lks. dist. mkd. T24S R6W S18 BT.
A Laurel 12" dia., bears S.76°W., 35 lks. dist. mkd. T24S R7W S13 BT.
A Laurel 8" dia., bears N.25°W., 22 lks. dist. mkd. T24S R7W S12 BT.

Survey by R.C. Grant - Wit: Geo. W. McHugill and Chas. C. Gilman - Jan. 26, 1954 - C.S. File 41/321

Renewed from O.B.T. stump, showing original scribes.
Marked new BTs:
17" Madrone N.36°W., 50.5 ft.
10" W.Fir N.83°E., 18.0 ft.
32" D.Fir S.26½°E., 69.5 ft.
38" W.Fir S.31°20'W., 26.2 ft.

Survey by Don E. Garrett - For: Resort Properties - Aug. 2, 1966 - M 33-8

Found - 1/2" I.P. by Grant.
12" W.Fir bears N.38°E., 18.0 ft.
17" Madrone N.36°W., 50.5 ft., now short snag.
Two Fir BTs down.
New BT - 12" Fir bears S.74°30'E., 59.4 ft. scribed S18 BT

(Cont. Next Page)

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 12 & 13; 7 & 18, T24-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Resurvey by W. Rogers & R. Browning - May/June 1993
under group #1687, (DCSO records Vol 51 pg 19535)

-
- Found - 1/2" dia. iron pipe firmly set, 4" above ground
 - Grand Fir, 27" dia. bears N.85°E., 28 lks. dist.
with a healed blaze.
 - Grand Fir, 22" dia. bears S.74°E., 90 lks. dist.,
with a healed double blaze.
 - Madrone, 28" dia., bears N.73°W., 30 lks dist., with
a healed blaze. (no previous record)
 - Set - Stainless steel post, 28" long, 2½" dia. 24" in
ground with brass cap marked:

T24S
R7W R6W
S 12 | S 7
S 13 | S 18
1993

New BT- Fir, 12" dia. bears S.24°W., 14 lks. dist, marked
"T24S R7W S13 BT"
Deposit the iron pipe inside and a white "deep-1" magnetic
marker at base of stainless steel post.

Fd. & used on BLM Dependent resurvey by Dale Bedell,
Cadastral Surveyor, under Group #1728, surveyed May 1994-
April 1995 - (DCSO records Vol. 52 Page(s) 19831-2)

Ron Rice - Josh Reed - 7/8/2010 - C.S. File 65/69-45

Condition Report only

Found - 3¼" BLM brass cap dated 1993 with the following
accessories:

- 30" W.Fir bears N.85°E., 18.5' - healed face.
- 30" Madrone bears N.73°W., 19.8' - healed face.
- 25" W.Fir bears S.74°E., 59.4' - healed face.
- 17" D.Fir bears S.24°W., 9.2' - healed face.

Note - Corner has steel post adjacent to it. All BTs have
red painted bands & yellow tag.

Fd. BC & 4 BTs by K Hoffine, 5/2014 - M168-11