

TOWNSHIP 24 RANGE 07 POINT IDENTIFIER # 700540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Sec. 12; & 7 of T24-6

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Robert Elder and Henry Gile, Deputy Surveyors,
under Contract #31 dated April 7, 1853 (DCSO records Vol. 8
Pg. 3127)

Set 1/4 Sec. post from which:

- A Fir, 40" dia., bears S.55°E., 30 lks. dist.
- A Fir, 13" dia., bears S.72°W., 25 lks. dist.

BLM Resurvey by W. Rogers & R. Browning - May/June 1993 under
group #1687, (DCSO records Vol. 51 Pg. 19536)

The 1/4 sec. cor. of secs. 7 and 12, reestablished by
proportionate measurement by the International Paper Co. in
1971 (as per records obtained from International Paper Co.).
There is no remaining evidence of the original corner,
therefore, this position is accepted as the corner,
monumented with an iron pipe, 1 in. dia., firmly set,
projecting 20 ins. above ground, from which the reference
trees by International Paper Co.:

Found Bearing Trees -

- A Fir, 13" dia., bears N.33½°E., 15 lks. dist., with a
metal International Paper Co. Tag.
- A Fir, 18" dia., bears N.32°W., 31 lks. dist., with a
metal International Paper Co. Tag.

Set - A stainless steel post, 28" long, 2½" dia. 25 " in the
ground, with brass cap mkd.

T24S

R7W R6W

1/4

S 12 S 7

1993

New Bearing Trees -

- A Fir, 15" dia., bears N.73°E., 15½ lks., mkd. "¼ S7 BT"
- A Fir, 12" dia., bears S.17°W., 30 lks., mkd. "¼ S12 BT"

Deposit the iron pipe inside and a white "DEEP-1" magnetic
marker at base of stainless steel post.