

PRIMARY CORNER DESCRIPTION SW. Cor. Sec. 31 (SW Tsp. Cor)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 8 Page(s) 3297)

Set Maple post 4 ft. long, 5" dia., 18" in ground for cor. to Tps. 24 and 25 S., R's 8 and 9 W., from which
A Cedar 10" dia., bears N.20°E., 30 lks. dist.
A Maple 8" dia., bears S.40°E., 10 lks. dist.
A Fir 48" dia., bears S.55°W., 68 lks. dist.
A Fir 60" dia., bears N.60°W., 24 lks. dist.

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3307)

Found tsp. cor., which is a post 4" sq., 2 ft. above ground mkd. T24S S31 on NE.; R8W S6 on SE.; T25S S1 on SW.; and R9W S36 on NW. faces, with 6 notches on each edge, from which
A Cedar 10" dia., bears N.20°E., 30 lks. dist. mkd. T24S R8W S31 BT.
A Maple 8" dia., bears S.40°E., 10 lks. dist. mkd. T15S R8W S6 BT.
A Fir 48" dia., bears S.56°W., 68 lks. dist. mkd. T25S R9W S1 BT.
A Fir 60" dia., bears N.60°W., 24 lks. dist. mkd. T24S R9W S36 BT.

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 8 Page(s) 3387)

At the cor. to Tp. 24 S., R. 8 W., which is a post, nearly decayed, bearing trees in good condition, otherwise marked and witnessed as described by the surveyor general. I re-establish this cor. as follows:
At this exact point where old Tp. cor. stood, I Set a new Cedar post, 3 ft. long, 4" sq., 24" in the ground, for cor. of Tp. 24 S., Rs. 8 and 9 W., marked: T24S R8W S31 on N. and W. edges, from which
A Cedar 10" dia., bears N.20°E., 30 lks. dist. mkd. T24S R8W S31 BT.
A Fir 60" dia., bears N.60°W., 24 lks. dist. mkd. T24S R9W S36 BT.
I destroy all markings on old bearing trees to the SE. and SW.

(Cont. Next Page)

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION SW. Cor. Sec. 31 (SW Tsp. Cor.)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Resurvey by James E. Jelly; Harvey E. Wofford; Wayne L. Rogers, Cadastral Surveyors, under Group #'s 926 and 958 - Surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16436)

Point for the cor. of Tps. 24 S. Rs. 8 and 9 W., at proportionate distance in departure, and at record distance in latitude, from the ¼ sec. cor. of secs. 31 and 36, Tps. 24 S., Rs. 8 and 9 W.; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 24 S
R 9 W R 8 W
S 36 S 31
T 25 S R 8 W
S 6
1979

from which

A Fir 16" dia., bears N.39½°E., 36 lks. dist. mkd. T24S R8W S31 BT.

A Fir 12" dia., bears N.17°W., 51 lks. dist. mkd. T24S R9W S36 BT.