

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 100473

PRIMARY CORNER DESCRIPTION CC Cor. Secs. 12 & 13 T24-9 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 8 Page(s) 3300)

Set maple post 3 ft. long, 5" dia., 18" in the ground for cor. to secs. 12 & 13 on east bdy, from which
A fir, 10" dia., bears N.35°E., 34 lks.
A fir, 16" dia., bears S.80°E., 14 lks.
A fir, 8" dia., bears S.45°W., 17 lks.
A fir, 16" dia., bears N.15°W., 17 lks.

Tony Hostetter - Feb. 2011 - C.S. File 65/72-4

Found - ½" conduit (1962 Weyerhaeuser records indicate that 2 orig GLO BTs were fd., a ½" conduit was set at that time.) from which:
30" Fir stump, possible face, bears: S.80°E., 9.2 ft to center. (GLO: 16" Fir, S.80°E., 14 lks)
New BTs- 16" Fir, WEYCO tag, bears: S.40°E, 10.5 feet to 12" spike, placed in top center of stump.
16" Fir, WEYCO tag, bears: S.08°W., 8.8 ft. to 6" spike, placed in root collar.
14" Hemlock stump, WEYCO tag, bears; West, 17.2 ft. to 6" spike, placed in root collar.