

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 100500

PRIMARY CORNER DESCRIPTION CC Secs. 7 & 18 T24-8 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by - Henry L. Chandler, Deputy Surveyor, Under Contract No. 619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3310-1)

Set a post 4½ ft. long, 4" sq., 24" in the ground for cor. to Secs. 7 & 18. T24S R8W marked T24S S7 on NE, and R8W S18 on SE faces with 4 notches on South and 2 notches on North edges, from which
A fir, 16" dia. bears N.76°E. 116 lks. mkd: T32S R1W S7 BT
A fir, 18" dia. bears S.39°E. 54 lks. mkd: T32S R1W S18 BT
A fir, 40" dia., bears S.45°W., 25 lks., mkd: T32S R1W S7 & 18 BT.

Tony Hostetter - Feb. 2011 - C.S. File 65/72-3

Found - 3/4" iron pipe (1962 Weyerhaeuser records indicate that 2 orig. GLO BTs were fd, a ½" conduit was set at that time. from which:
38" Fir stump, possible face, WEYCO tag, bears: N.76°E., 74.5 ft to center. (GLO: 16" Fir, N.76°E, 116 lks)
48" Fir stump, no marks, WEYCO tag, bears: S.45°W., 19.0 ft to center. (GLO: 40" Fir, S.45°W. 25 lks)
22" Hemlock stump, WEYCO tag, bears; N.81°E., 53.3 ft to center.
New BTs- 14" Fir, WEYCO tag, bears: S.85°E., 41.2 ft to 12" spike, placed in top center of stump.
12" fir, WEYCO tag, bears: S.65°E., 16.8 ft TO 12" spike, placed in top center of stump.