

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 136100

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. Sec. 6 only, T25-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Survey by Donald L. Peel - For: Weyerhaeuser Co. - May 1967
C.S. File 55/30-4

(Set by single proportionate measurement)
Set 4 ft. x 3/4" pipe, 3 1/2 ft. in ground and square post.
Referenced the Weyerhaeuser method (W" nail, disc, plate):
16" Fir S.6°W., 15.1 ft.
36" Cedar N.66°W., 12.2 ft.

Douglas Co. Surveyors Office - Aug. 27, 1970 - C.S. File
54/72-51

Found unrecorded 32" Cedar snag facing N.50° to 60°W. with
old scribe "1/4 S6 BT". "W" nail and tag near base of tree. We
find no trace of orig. Hemlock BT. By measuring 1/2 chain or
33.0 ft. West from creek, we find the Cedar faces this point,
also 30" Maple bears N.20°E., 24.4 ft. as in the field notes
but the center of this tree is decayed out for more than the
orig. 6" size. This point is 20.0 ft. South of
Weyerhaeuser's line that is mkd. "true line". Weyerhaeuser's
proportioned N. 1/4 cor. of sec. 6 bears N.76°W., 84.0 ft.
From same point, We set temporary post from 30" maple. The
32" Cedar bears S.58°E., 19.6 ft.
*(Note: I believe the 30" Maple, N.20°E. tree to be a BT for
the So. 1/4 Cor. Sec. 31 only (established by Chandler, 1893)
and made into So. 1/4 Cor. only by Wygant in 1911) V. Laugen,
March 1997)*

BLM Resurvey by James E. Jelly; Harvey E. Wofford; Wayne L.
Rogers, Cadastral Surveyors, under Group #'s 926 and 958 -
Surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s)
16435-36 and 16461-62)

(Page 16435-36) (3.92 chs.)
(Found corner established by Peel)

(Page 16461-62) (3.96 chs.)
The point for the 1/4 sec. cor. of sec. 6 only, is at
proportionate distance on the N. bdy. of sec. 6.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground,
with brass cap mkd: T 24 S R 8 W

1/4 S 6
T 25 S R 8 W
1979

from which
(Cont. Next Page)

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 136100

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 6 only, T25-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Hemlock 20" dia., bears S.2½°W., 39 lks. mkd. ¼ S6 BT.
A Cedar 43" dia., bears S.63¾°W., 17 lks., mkd. ¼ S6 BT.

Tony Hostetter - For: Weyerhaeuser Co. - Nov. 2013 - M167-6

Found - 1979 BLM Cap as described vol. 42, pg. 16435-36.
43" Cedar stump, scribing bears; S.63¾°W., 14 lks.
3/4" iron pipe by Peel (CS 55/30) bears; S.13°44'E,
11.14'
New BTs- 40" Cedar, scribed, S6 ¼ BT", BT TAG, bears;
S.04°43'E., 40.2 ft. to spike.
13" Hemlock, scribed "S6 ¼ BT", BT TAG bears;
S.17°36'W, 9.2 ft to spike.