

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 and 32 only (South)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3306)

Set a post 4 ft. long, 4" sq., 24" in the ground mkd. T24S S32 on NE.; R8W S31 on NW.; T25S S5 on SE.; and S6 on SW. faces, with 5 notches on E. and 1 notch on W. edges, from which

A Fir 72" dia., bears N.25°E., 56 lks. dist. mkd. T24S R8W S32 BT.

A Maple 10" dia., bears N.60°W., 23 lks. dist. mkd. T24S R8W S31 BT.

A Fir 36" dia., bears S.18°W., 56 lks. dist. mkd. T24S R8W S31 and 32 BT.

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 8 Page(s) 3386)

(70.40 chs.)
Old sec. cor. in place; post and bearing tree mkd. and witnessed as described by the surveyor general. I destroy the post, and cut out all marks on bearing trees.

(84.75)
Cor. of secs. 5, 6, 31 and 32 established in 1894, contract #619, and which is a post, firmly set, mkd. and witnessed as described by the surveyor general, bears N. 95 lks. dist. I destroy marks on post and bearing trees referring to secs. 5 & 6.

Survey by Henry R. Reppeto - For: Weyerhaeuser Co. - March 6, 1975 - C.S. File 58/45

Set 2" x 3 ft. Iron pipe, 2 ft. in the ground with a brass cap stamped "SW S32". Referenced by:

15" Cedar N.74°E., 14.4 ft. "W" nail, W.Co. tag reads:
Sec. 32 T24S R8W 14.4 ft. S.74°W. to SW. Cor.; scribed S32 BT

12" Cedar N.49°E., 19.5 ft. "W" nail, W.Co. tag reads:
Sec. 31 T24S R8W 19.5 ft. S.49°E. to SW. Cor. scribed S31 BT.

BLM Resurvey by James E. Jelly; Harvey E. Wofford; Wayne L. Rogers, Cadastral Surveyors, under Group #'s 926 and 958 - Surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16434)

(Cont. Next Page)

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 200100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The Cor. of secs. 31 and 32 only, determined at record brg. and dist. from the remains of an orig. bearing tree:

A decayed Fir snag 40" dia., bears N.25°E., 56 lks. dist. with scribe marks 8W BT visible on decayed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 24 S R 8 W
S 31*S 32
T 25 S R 8 W
S 5
1979

from which new bearing trees

A Hemlock 8" dia., bears N.34°E., 82 lks. dist. mkd. T24S R8W S32 BT.

A Hemlock 11" dia., bears N.2½°W., 51 lks. dist. mkd. T24S R8W S31 BT.

(At 0.12 chs.) (S.89°52'W.)

From this point, a corner established and recorded by Reppeto, in 1975, bears North, 0.06 chs. dist. monumented with an iron post 1½" dia., firmly set, projecting 12" above ground with brass cap mkd. SW S32

from which the remains of bearing tree mkd. by Reppeto

A Cedar 14" dia., bears N.72°E., 23 lks. dist. with scribe marks S32 BT visible on open blaze.

A sawed Cedar stump 10" dia., bears N.51°W., 30 lks. dist. with scribe marks S31 BT visible on open blaze.

Tony Hostetter - For: Weyerhaeuser Co. - Nov. 2013 - M167-6

Found - 1979 BLM cap and BTs as described Vol. 42, pg. 16434.

1975 WEYCO cap by Reppeto bears; N.62°32'W., 8.88 ft.

Both BTs now stumps.