

PRIMARY CORNER DESCRIPTION Sec. Cor. for 29, 30, 31 and 32

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCS0 records Vol. 8 Page(s) 3366)

Set a sandstone 14 x 12 x 7 ins., 9" in the ground, for cor. to secs. 29, 30, 31 and 32, marked with 1 notch on S. and 5 notches on E. edges, from which

- A Laurel 12" dia., bears N.34°E., 36 lks. dist. mkd. T24S R8W S29 BT.
- A Cedar 18" dia., bears S.65°E., 37 lks. dist. mkd. T24S R8W S32 BT.
- A Laurel 16" dia., bears S.60°W., 20 lks. dist. mkd. T24S R8W S31 BT.
- A Fir 12" dia., bears N.13°W., 31 lks. dist. mkd. T24S R8W S30 BT.

BLM resurvey by C. Albert White;, Cadastral Surveyor and Donald R. Beck, Surveying Technician - under Group #427, Surveyed July/Aug. 1962 - (DCS0 records Vol. 32 Page(s) 13331-32)

The Sec. cor., determined at record distance from the remains of three original bearing trees and at the intersection of the original N. and S. and E. and W. blazed lines: from which the original bearing trees:

- A Madrone stump hole bears N.50°E., 36 lks. dist. (Rec. N.34°E.)
- A burned Fir snag 14" dia., bears S.60°E., 44 lks. dist. (Rec. a Cedar 18" dia. S.65°E., 37 lks. dist.)
- A Madrone stump hole bears S.64°W., 20 lks. dist. (Rec. S.60°W.)
- A rotted Fir stump bears N.23°W., 31 lks. dist. (Rec. N.13°W.)

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 24 S R 8 W			
S 30		S 29	
S 31		S 32	
1962			

from which

- A Madrone 13" dia., bears N.48½°E., 34 lks. dist. mkd. T24S R8W S29 BT.
- A Fir 8" dia., bears S.32½°E., 45 lks. dist. mkd. T24S R8W S32 BT.
- A Fir 18" dia., bears S.36°W., 44 lks. dist. mkd. T24S R8W S31 BT.

(Cont. Next Page)

