

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 19 and 20

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3372-73)

Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on W. face, from which
A Fir 14" dia., bears S.85°E., 16 lks. dist. mkd. ¼ S BT
A Fir 20" dia., bears S.58°W., 31 lks. dist. mkd. ¼ S BT

BLM corner remonumentation by Harold D. Corbin, Cadastral Surveyor, under Group #'s 350 and 427, Surveyed June 1959 - (DCSO records Vol. 30 Page(s) 12616)

The ¼ sec. cor. determined at record bearing and distance from the original SE. bearing tree:
A Fir 24" dia., bears S.85°E., 16 lks. dist. with scribe marks BT visible on partially opened blaze.
and a bearing tree which does not match the record:
A Fir 30" dia., bears N.53¼°W., 28 lks. dist. with scribe marks 4 S B visible on opened blaze. (Rec. S.58°W., 31 lks.)

At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 24 S R 8 W
¼
S 19 S 20
1959

from which
A Fir 28" dia., bears N.49¼°E., 49 lks. dist. mkd. ¼ S20 BT.
A Fir 27" dia., bears S.78½°W., 38 lks. dist. mkd. ¼ S19 BT.

Survey by Nick Juliano - For: Weyerhaeuser Co. - Sept. 1969 -C.S. File 55/120 and M 38-48

Found - BLM brass cap.
28" Fir N.49½°E., 49 lks.
24" Fir stump N.78½°W., 36 lks.
Referenced with "W" nails and plates:
26" Fir S.87°E., 10.7 ft.
22" Fir stump N.52°W., 17.2 ft.