

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3373)

-----  
Set a sandstone 14 x 8 x 6 ins., 9" in the ground for cor. to secs. 17, 18, 19 and 20, marked T24S S17 on NE.; R8W S20 on SE.; S19 on SW.; and S18 on NW. faces, with 3 notches on S. and 5 notches on E. edges, from which  
A Hemlock 8" dia., bears N.44°E., 53 lks. dist. mkd. T24S R8W S17 BT.  
A Maple 12" dia., bears S.60°E., 40 lks. dist. mkd. T24S R8W S20 BT.  
A Maple 12" dia., bears S.77°W., 21 lks. dist. mkd. T24S R8W S19 BT.  
A Hemlock 18" dia., bears N.52°W., 35 lks. dist. mkd. T24S R8W S18 BT.

Douglas Co. Surveyors Office - John M. Powell, W. Penley; J. Heritage, crew - Sept. 13, 1971 - C.S. File 54/55-28

-----  
Found - 18" Hemlock, now 21" D.Fir snag, N.52°W., 23.1 ft., opened before, scribe visible "24". Opened tree more for "BT", rings too close for count.  
Possible BT stob, level with ground, N.44°E., 35.0 ft.  
No trace of Maple bearing tree.  
Stone found, out of ground about 3 ft. N. of corner with 3 & 5 notches.

Set Brass cap at cor. mkd: County Surveyors Office  
T 24 S R 8 W  
S 18 | S 17  
S 19 | S 20  
1971

New BTs- 18" Tan Oak S.21°E., 33.4 ft. scribed T24S R8W S20 CS BT.  
38" D.Fir S.11°W., 39.0 ft. scribed T24S R8W S19 CS BT.  
39" D.Fir N.21°E., 65.8 ft. scribed T24S R8W S17 CS BT.  
40" D.Fir N.82°W., 21.3 ft. scribed T24S R8W S18 CS BT.

Call to creek hit good by pacing approx. 7 chs. to West.

continued next page

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 200400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 17, 18, 19 and 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Tony Hostetter - For: WEYCO - April 2012 - C.S. File 65/77-16  
-----

Found - 1971 DCSO brass cap as described county records.  
40" fir stump, face evident, DCSO BT bears; S.11°W.,  
39.0 ft.  
40" Fir stump, no marks, WEYCO BT, bears; N.74°E.,  
18.2 ft to "W" nail.  
New BTs- 17" Fir stump (4' tall), WEYCO tag, bears; N.72°E.,  
11.6 ft to spike in root collar.  
16" Fir stump (4' tall), WEYCO tag, bears; S.33°E.,  
22.9 ft to spike in root collar  
16" Fir stump, WEYCO tag, bears; S.06°E, 22.9 ft to  
spike in root collar.