

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 200440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 17 and 18

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3376)

Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on W. face, from which

A Hemlock 6" dia., bears S.54°E., 19 lks. dist. mkd. ¼ S BT.

A Hemlock 14" dia., bears West, 24 lks. dist. mkd. ¼ S BT.

Survey by Donald L. Peel - For: Weyerhaeuser Co. - March 1967
C.S. File 55/30-2

Found - GLO survey record, post gone.

14" Hemlock, West 34 lks., now 24" Hemlock, face visible, scribe part rotted out, cruiser's marks.

6" Hemlock S.34°E., 19 lks., now 26" W.Fir (not Hemlock) Could not see any face, base of tree buried by road construction.

Set 3/4" x 4 ft. Pipe, 3½ ft. into ground.

Original BTs marked with Weyerhaeuser tags.