

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3376)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 7, 8, 17 and 18, marked, T24S S8 on NE.; R8W S17 on SE.; S18 on SW.; and S7 on NW. faces, with 4 notches on S. and 5 notches on E. edges, from which

A Fir 7" dia., bears N.12°E., 36 lks. dist. mkd. T24S R8W S8 BT.

A Fir 40" dia., bears S.49°E., 50 lks. dist. mkd. T24S R8W S17 BT.

A Fir 36" dia., bears S.12°W., 48 lks. dist. mkd. T24S R8W S18 BT.

A Fir 12" dia., bears N.41½°W., 30 lks. dist. mkd. T24 S R8W S7 BT.

Douglas Co. Surveyors Office - John M. Powell, W. Penley & J. Heritage, crew - Sept. 14, 1971 - C.S. File 54/55-29

Found - 7" now 13" D.Fir N.15°E., (Rec. N.12°E.) 23.8 ft., no scar, tree opened.

36" now 40" D.Fir S.12°W., 28.7 ft. (Rec. 31.7 ft.), shows good scar.

12" now 18" D.Fir N.41½°W., 19.8 ft., tree opened, scribe visible.

40" D.Fir now down, S.49°E., 33.0 ft., shows scar.

Set Brass cap at cor. mkd: County Surveyors Office

T	24	S	R	8	W
	S	7		S	8
	S	18		S	17
					1971

Reblazed and rescribed:

13" D.Fir N.15°E., 23.8 ft. scribed "S8 CS BT"

New BT - 8" Dogwood S.73½°E., 12.0 ft. scribed "T24S R8W S17 CS BT"

Draw bears E. approx. 1 chain and top of ridge bears N. approx. 3 chains as noted in 1951 forest appraisal.

Tony Hostetter - For: Weyerhaeuser Co. - Feb. 2020 - C.S. File 65/106-8

Found - 1971 DCSO brass cap 40" Fir stump, OBT, no marks. bears S.12°W., 28.7 ft to center. (GLO record S.12°W, 31.7 ft) (DCSO 1971 S.12°W., 28.7 ft)

18" Fir stump, OBT, no marks. bears N.45°W., 19.8 ft to center. (GLO record N.41½°W., 19.8 FT)

continued next page

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 7, 8, 17 and 18

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New BTs- 14" Fir stump, BT tag, bears N.53°E., 16.3 ft to 6" spike, placed below tag.
15" Fir stump, BT tag, bears S.14°E., 15.6 ft to 6" spike, placed below tag. 13" Fir stump, BT tag, bears N.28°W. 4.4 ft to 6" spike placed below tag