

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William R. Whipple, Deputy Surveyor, under Contract #622, dated June 23, 1893 (DCSO records Vol. 6 Page(s) 2556-57)

Set a post 4 ft. long and 4" sq., 2 ft. in the ground for cor. to secs. 31 and 32 marked T23S R8W on N.; S32 on E.; and S31 on W. edges with 5 notches on E. and 1 notch on W. edges, from which

A Hemlock 20" dia., bears N.55°E., 45 lks. dist. mkd. T23S R8W S32 BT.

A Hemlock 5" dia., bears N.20°W., 3 lks. dist. mkd. T23S R8W S31 BT.

A Hemlock 24" dia., bears S.18°E., 55 lks. dist. mkd. T23S R8W S31 and 32 BT.

Remonumentation of corners by Joseph P. Gawron, Cadastral Surveyor, under Group #(?), Surveyed 1963 - DCSO Records, Vol. 33 Page 13872

The cor. of secs. 31 and 32 only, determined at record distance from the remaining original bearing trees:

A burned Hemlock stump, size indeterminate, bears N.55°E., 45 lks. dist., with no marks remaining.

A Hemlock snag, 30" dia., bears S.16½°E., 55 lks. dist., with partial scribe marks visible. (Rec. S.18°E.)

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 23 S R 8 W	
<u>S 31</u>	<u>S 32</u>
S	5
T 24 S	
1963	

from which

A Hemlock 5" dia., bears N.37°E., 101 lks. dist. mkd. T23S R8W S32 BT.

A Hemlock 9" dia., bears N.34½°W., 56 lks. dist. mkd. T23S R8W S31 BT.

Douglas County Surveyors Office - Vernon "Ray" Tracy and crew Jan. 1967 - C.S. File 54/12-21

Found - 1963 Cadastral brass cap, properly marked.
Orig. 30" Hemlock, now burned stump, S.16½°E., 36.8 ft.

1963 5" Hemlock, dead and burned, N.37°E., 66.7 ft., scribe visible.

1963 9" Hemlock, N.34½°W., 37.0 ft., now burned stump, scribe visible. (Cont. Next Page)

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 201700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 31 & 32 only T23-8

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

New BTs- 6" Hemlock N.27°E., 67.8 ft. mkd. T23S R8W S32 CSBT
9" Hemlock N.35½°W., 90.4 ft. mkd. T23S R8W S31 CSBT
Corner lies on small bench on westerly slope of small stream,
course SE., in large logged-off unit.

Tony Hostetter - For: Weyerhaeuser Co. - July 2003 - M142-67

Found - 1963 brass cap & accessories as described by Tracy
in 1967 - C.S. 54/12
10" Fir, WEYCO tag, bears N.11°W., 0.8 ft.
New BTs- 16" Fir, scribed "S32 SW BT" bears S.49°E., 6.0 ft.
to spike.
14" Fir, scribed "S31 SE BT" bears S.59°W., 23.0 ft.
to spike.