

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 8 Page(s) 3296)

Set Dogwood post 40" long, 5" dia., 18" in ground for the qr. sec. cor. on S. bdy. of sec. 32, from which
A Fir 40" dia., bears S.89°E., 81 lks. dist.
A Maple 10" dia., bears N.85°W., 17 lks. dist.

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3305)

(29.42 chs.)
The old ¼ sec. cor. (found as described above)
(40.00 chs.) (West)
Set a post 3½ ft. long, 3" sq., 24" in the ground for ¼ sec. cor. on So. bdy. Sec. 32, mkd. ¼ S on N. face, from which
A Hemlock 6" dia., bears N.27°E., 31 lks. dist. mkd. ¼ S BT
A Hemlock 8" dia., bears S.34°W., 42 lks. dist. mkd. ¼ S BT.

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 8 Page(s) 3385)

(At 29.42 and 41.45 chains), "No trace of old ¼ sec. cor. can be found after diligent search".

Survey by Henry R. Reppeto - For: Weyerhaeuser Co. - March 6, 1975 - C.S. File 58/45

Set 2" x 3 ft. Iron pipe 2 ft. in the ground with brass cap stamped S¼ S32. Referenced by:
12" Fir N.50°30'E., 56.1 ft. "W" nail, W. Co. tag reads: Sec.32 T24S R8W 56.1 ft. S.50°30'W. to S ¼ Cor., scribed ¼ S32 BT.
72" Fir N.30°W., 70.3 ft. "W" nail, W. Co. tag reads: Sec. 32 T24S R8W 70.3 ft. S.30°E. to S ¼ Cor., scribed ¼ S32 BT.

BLM Resurvey by James E. Jelly; Harvey E. Wofford; Wayne L. Rogers, Cadastral Surveyors, under Group #'s 926 and 958 - Surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16433)

(Cont. Next Page)

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 240100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 32 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The ¼ sec. cor. of sec. 32 only, reestablished by proportionate measurement and recorded by Reppeto in 1975, and is accepted as the best available evidence of the position of the original corner, monumented with an iron post, 1½" dia., firmly set, projecting 8" above ground with brass cap mkd. S 1/4

S 32

from which the remains of bearing trees mkd. by Reppeto

A Fir snag 10" dia., bears N.50½°E., 85 lks. dist. with scribe marks ¼ S32 BT visible on open blaze.

A Fir 70" dia., bears N.30°W., 112 lks. dist. with scribe marks ¼ S32 BT visible on bark.

and a new bearing tree

A Fir 20" dia., bears N.40°E., 112 lks. dist., mkd. ¼ S32 BT.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 3/23/26 - C.S. File 67/62-29

Found - 2" pipe cap on iron pipe, proj. 6".
11" x 2 ft. metal capped fir stump N.50½°E. 56.1 ft. marks rotted.

Very rotten 60" x 5 ft. D. fir stump N.30°W. 73.9 ft. (B & D not checked.)

21" x 5 ft. metal capped fir stump N.40°E. 73.9 ft. partly healed single blaze, scribes visible.

Steel fence post 1 ft. east.

New - 19" D. Fir S.67°E. 60.4 ft. scribed ¼ S32 on double blaze.

26" D. Fir S.41°W. 14.3 ft. scribed ¼ S32 on double blaze.

19" D. Fir N.87°W. 34.8 ft. scribed ¼ S32 on double blaze.

3½" mag nail right side center of new trees.

Notes - Mon. approx. 30 ft. west of gravel road.

Mon. is on nearly flat ground in very old reprod.

Compass decl. 14¼°E.

TRIMBLE GEO XT LOCATION

43°.43266441 N. 123°.67338432 W.