

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 29 and 32

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3367)

Set a sandstone 14 x 12 x 6 ins., 9" in the ground for ¼ sec. cor. marked ¼ on N. face, from which
A Fir 60" dia., bears N.33°E., 66 lks. dist. mkd. ¼ S BT.
A Fir 60" dia., bears S.70°W., 80 lks. dist. mkd. ¼ S BT.

BLM resurvey by C. Albert White;, Cadastral Surveyor and Donald R. Beck, Surveying Technician - under Group #427, Surveyed July/Aug. 1962 - (DCSO records Vol. 32 Page(s) 13330-31)

The ¼ sec. cor., monumented with a sandstone 16x12x10 ins., firmly set 2" in the ground mkd. ¼ on S. face, from which the original bearing trees:

- A burned Fir snag 62" dia., bears N.30°E., 63 lks. dist. (Rec. N.33°E., 66 lks.)
- A Fir 80" dia., bears S.72°W., 77 lks. dist. mkd. with a bark blaze. (Rec. S.70°W., 80 lks. dist.)

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 18" in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

¼ $\frac{S\ 29}{S\ 32}$
T 24 S R 8 W
1962

from which new bearing trees

- A Fir 22" dia., bears N.71°W., 20 lks. dist. mkd. ¼ S29 BT.
 - A Fir 27" dia., bears S.¼°E., 106 lks. dist. mkd. ¼ S32 BT
- Deposit original corner stone alongside the iron post.

Fd. OK, Nov. 1983 by H. Johnstone - M 95-41