

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 240300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 20 and 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3370)

-----  
Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on N. face, from which  
A Hemlock 10" dia., bears S.18½°E., 6 lks. dist. mkd. ¼ S BT.  
A Fir 48" dia., bears N.11°W., 38 lks. dist. mkd. ¼ S BT.

BLM resurvey by C. Albert White;, Cadastral Surveyor and Donald R. Beck, Surveying Technician - under Group #427, Surveyed July/Aug. 1962 - (DCSO records Vol. 32 Page(s) 13333)

-----  
The ¼ sec. cor., determined at record bearing and distance from the original bearing trees:  
A downed Fir bears N.11°W., 38 lks. dist. no marks visible.  
A Hemlock 22" dia., bears S.18½°E., 6 lks. dist. mkd. with a healed blaze and cruiser marks. Reblaze and mark ¼ S29 BT.

At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:  
¼ S 20  
S 29  
T 24 S R 8 W  
1962

from which a new bearing tree  
A Fir 12" dia., bears N.12½°E., 76 lks. dist. mkd. ¼ S20 BT.