

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 240340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Nick Juliano - For: Weyerhaeuser Co. - Sept. 1969
-C.S. File 55/120 and M 38-48

The center of sec. 20 was determined by the intersection of
the N-S and E-W center lines of said section.
Set 2" Iron pipe with brass cap.
Referenced with "W" nails:
 36" Fir S.21°W., 19.2 ft.
 40" Fir N.22°E., 9.3 ft.

Tony Hostetter - For: Weyerhaeuser Co - 3/2006 - CS 65/58-10

Found - 2" iron pipe w/brass cap & both BTs set by Juliano
in 1969 (M 38-48).
New BTs- 18" hemlock, scribed "S20 C¼ BT", tagged, bears;
 S.60°E., 33.9 ft to spike placed below scribing.
 12" hemlock, scribed "S20 C¼ BT", tagged, bears
 N.27°W., 43.8 ft to spike placed below scribing.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and
Jeff Lorsung - 3/19/26 - C.S. File 67/62-26

Found - 3½" unstamped brass cap on iron pipe.
 20" hemlock S.60°E. 33.9 ft. to spike in face below scribes
 Partly healed single blaze. Illegible scribes visible.
 16" hemlock N.27°W. 43.8 ft. to spike in face. Partly
 healed single blaze, scribing visible.
UNRECORDED - 65" D. Fir S.21°W. 19.2 ft. Not blazed but tagged. 3½"
 mag nail in face.
Compass decl. 14¼°E.
TRIMBLE GEO XT POSITION
43°.46851352 N. 123°.67348987 W.