

PRIMARY CORNER DESCRIPTION 1/4 cor. for Sec. 17 and 20

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3374)

-----  
Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on N. face, from which  
A Fir 60" dia., bears North, 29 lks. mkd. ¼ S BT.  
A Fir 36" dia., bears S.87°W., 61 lks. dist. mkd. ¼ S BT.

Survey by Donald L. Peel -For: Weyerhaeuser Co. - March 1967 - C.S. File 55/30-2

-----  
Found - GLO survey record, post, gone.  
60" Fir, North 29 lks., now 72" Fir, cruiser marks.  
30" Fir S.87°W., 61 lks., now 48" Fir, face visible, healed over.  
Set 3/4" x 4 ft. pipe, 3½ ft. in ground.  
Marked original BTs with Weyerhaeuser tags.

Tony Hostetter - For: Weyerhaeuser Co - 3/2006 - C.S. 65/58-8

-----  
Found - 1/2" aluminum pipe. (Not ¾" described by Peel as CS 55/20) from which:  
72" fir stump, OBT, WEYCO tag and "W" nail, bears North, 19.1 ft.  
48" fir stump, face evident, bears S.87°W., 35.1 ft (record 40.3 ft.)  
New BTs- 18" fir, scribed "S17 ¼ BT", tagged, bears; N.08°E., 73.5 ft to spike placed below scribing.  
10" fir, scribed "S20 ¼ BT", tagged, bears S.22°W., 14.8 ft to spike placed below scribing.