

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 240500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3377)

-----  
Set a sandstone 24 x 18 x 5 ins., 18" in the ground for ¼ sec. cor. mkd. ¼ on N. face, from which

A Cedar 30" dia., bears N.80°E., 107 lks. dist. mkd. ¼ S BT.

A Hemlock 16" dia., bears S.86°E., 90 lks. dist. mkd. ¼ S BT.

Survey by Donald L. Peel - For: Weyerhaeuser Co. - March 1967 - C.S. File 55/30-2

-----  
Found - GLO survey record, sandstone, gone.

16" Hemlock S.86°E., 90 lks. gone.

30" Cedar N.80°E., 107 lks., found but had been knocked down during logging.

Set 3/4" x 4 ft. Pipe, 3½ ft. into ground.

Before logging, the corner had been re-referenced by R. Yantis of Weyerhaeuser Co. with a "W" nail and Weyerhaeuser tags.