

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 240700

PRIMARY CORNER DESCRIPTION No. 1/4 Cor. for Sec. 5 only

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 6 Page(s) 2539)

Set a post 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor. marked ¼ S on N. face, from which

A Hemlock 24" dia., bears N.67°E., 53 lks. dist. mkd. ¼ S BT.

A Hemlock 24" dia., bears S.85°E., 57 lks. dist. mkd. ¼ S BT.

Douglas Co. Surveyors Office - V.R. Tracey and crew - Jan. 21, 1967 - C.S. File 54/12-2

From ¼ cor. of S. 32, T23-8, we go West 89.8 ft. and from this point find the following possible BTs,

20" Hemlock stump approx. S.85°E., 27 ft. We open and find "BT" scribe also old "S" scribe on upper blaze.

36" Hemlock stump approx. N.67°E., about 30 ft. shows old scar.

Both stumps appear to be out of position due to logging.
Do Not Renew.

Tony Hostetter - For: Weyerhaeuser Co. - July 2003 - M142-67

Found - ¾" iron pipe set by Weyerhaeuser Co.

Both OBTs are stumps not in orig. position. WEYCO tag on Hemlock stump reads: S.67°W., 33.7 ft. (GLO: N.67°E., 35.0 ft)

48" Fir stump, WEYCO tag, bears S.01°E., 21.0 ft. to "W" nail.

40" stump, WEYCO tag, bears N.80°W., 23.7 ft. to "W" nail.

New BTs- 14" Fir, scribed "S4 ¼ BT" bears S.22°W., 3.5 ft. to spike.

12" Fir, scribed "S4 ¼ BT" bears S.58°E., 21.5 ft. to spike.