

PRIMARY CORNER DESCRIPTION C C for Sec. Cor. for 4 & 5 only, T25-8

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 8 Page(s) 3296)

Set Maple post 3 ft. long, 5" dia., 20" in ground for the cor. to secs. 32 and 33, from which
A Fir 24" dia., bears N.60°E., 28 lks. dist.
A Fir 48" dia., bears S.5°E., 39 lks. dist.
A Fir 30" dia., bears S.88°W., 90 lks. dist.
A Fir 30" dia., bears N.89°W., 105 lks. dist.

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3304)

The old established cor. to secs. 4, 5, 32 and 33, which is a post 4" sq., 2 ft. above ground, mkd. T24S S33 on NE.; T25S S4 on SE.; R8W S5 on SW. and S32 on NW. faces, with 4 notches on E. and 2 notches on W. edges, from which
(Found all four trees as described above)
I destroy marks on both post and trees referring to secs. 32 and 33.

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 10 Page(s) 3992-93)

Intersect the S. bdy. of T24S R8W, 3.01 chs., N.89°21'W. from cor. of secs. 32 and 33, I SET a Maple post 3 ft. long, 4" sq. 24" in the ground, for closing cor. of secs. 4 and 5, marked C C T25S R8W on S.; S4 on E.; and S5 on W. with 4 grooves on E. and 2 grooves on W. faces, from which
A Fir 32" dia., bears S.14°50'E., 62 lks. dist. mkd. T25S R8W S4 BT.
A Fir 30" dia., bears S.62°30'W., 70 lks. dist. mkd. T25S R8W S5 BT.

Survey by Henry R. Reppeto - For: Weyerhaeuser Co. - March 6, 1975 - C.S. File 58/45

Set Brass cap in rock outcrop, stamped NE S5, referenced by:
48" Fir S.66°E., 18.8 ft. "W" nail, W. Co. tag reads, Sec. 4 T25S R8W 18.8 ft., N.66°W., to NW. cor. scribed S4 BT.
58" Fir S.73°W., 81.0 ft. "W" nail, W. Co. tag reads Sec. 5 T25S R8W 81.0 ft. N.73°E. to NE. cor., scribed S5 BT.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION C C for Secs. 4 & 5 only, T25-8

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM Resurvey by James E. Jelly; Harvey E. Wofford; Wayne L. Rogers, Cadastral Surveyors, under Group #'s 926 and 958 - Surveyed Aug. 1977/April 1979 - (DCSO records Vol. 42 Page(s) 16456-57)

At true point for the closing cor. of secs. 4 and 5.
Set an iron post 28" long, 2½" dia., 22" in the ground with
brass cap mkd: T 24 S R 8 W

S 32

S 5 S 4
C C
T 25 S R 8 W
1979

from which bearing trees mkd. by Reppeto in 1975

A Fir 40" dia., bears S.61½°E., 35 lks. dist., with scribe marks S4 BT visible on bark blaze.

A Fir 45" dia., bears S.67°W., 124 lks. dist., with scribe S 5 BT visible on bark blaze.

From this point, a corner established and recorded by Reppeto bears S.70°30'E., 0.18 chs. dist., monumented with a brass tablet 2" dia., set in drill hole in exposed bedrock, mkd. NE S5.

From this same point, the original closing cor. of secs. 4 and 5, bears N.0°06'W., 0.17 chs. dist., determined from the remains of the original bearing trees:

A Fir stump 36" dia., bears S.9°E., 62 lks. dist., with scribe marks T25S R8 W S5 BT visible on opened blaze. (Rec. S.14°50'E.)

A root hole bears S.62½°W., 70 lks. dist. with a down Fir alongside 38" dia., with scribe marks 25S R8W S4 visible on partially open blaze.