TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 300140

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 32 and 33

Alias Description
Alias Description
Alias Description
Alias Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3353)

Set a sandstone 24 x 12 x 5 ins., 18" in the ground, for ¼ sec. cor. marked ¼ S on W. face, from which
A Fir 36" dia., bears N.46½°W., 100 lks. dist. mkd. ¼ S BT
A Laurel 16" dia., bears S.46½°E., 22 lks. dist. mkd. ¼ S BT.

BLM resurvey by C. Albert White;, Cadastral Surveyor and Donald R. Beck, Surveying Technician - under Group #427, Surveyed July/Aug. 1962 - (DCSO records Vol. 32 Page(s) 13323)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd: ¼
S 32 S 33
T 24 S R 8 W
1962
from which
A Fir 52" dia., bears S.87½°E., 56 lks. dist. mkd. ¼ S33 BT.
A Fir 38" dia., bears N.30°W., 37 lks. dist. mkd. ¼ S32 BT

Fd. OK, Nov. 1983 by H. Johnstone - M 95-41