

PRIMARY CORNER DESCRIPTION Sec. Cor. for 28, 29, 32 and 33

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3353)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 28, 29, 32, 33 marked, T24S S28 on NE.; R8W S33 on SE.; S32 on SW.; and S29 on NW. faces, with 1 notch on S. and 4 notches on E. edges, from which
A Fir 18" dia., bears N.75°E., 28 lks. dist. mkd. T24S R8W S28 BT.
A Fir 18" dia., bears S.12°E., 110 lks. dist. mkd. T24S R8W S33 BT.
A Fir 40" dia., bears S.57°W., 26 lks. dist. mkd. T24S R8W S32 BT.
A Yew 20" dia., bears N.50°W., 60 lks. dist. mkd. T24S R8W S29 BT.

BLM resurvey by C. Albert White;, Cadastral Surveyor and Donald R. Beck, Surveying Technician - under Group #427, Surveyed July/Aug. 1962 - (DCSO records Vol. 32 Page(s) 13324)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:
T 24 S R 8 W
S 29 S 28
S 32 S 33
1962

from which
A Fir 15" dia., bears N.15°E., 56 lks. dist. mkd. T24S R8W S28 BT.
A Fir 25" dia., bears S.33½°E., 57 lks. dist. mkd. T24S R8W S33 BT.
A Fir 18" dia., bears S.45°W., 26 lks. dist. mkd. T24S R8W S32 BT.
A Fir 13" dia., bears N.44°W., 6 lks. dist. mkd. T24S R8W S29 BT.

Fd. OK, Nov. 1983 by H. Johnstone - M 95-41