

PRIMARY CORNER DESCRIPTION Sec. Cor. for 20, 21, 28 and 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3355-56)

- 
- Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 20, 21, 28 and 29 marked, T24S S21 on NE.; R8W S28 on SE.; S29 on SW.; and S20 on NW. faces, with 2 notches on S. and 4 notches on E. edges, from which
- A Fir 18" dia., bears N.40°E., 84 lks. dist. mkd. T24S R8W S21 BT.
  - A Fir 16" dia., bears S.22¼°E., 19 lks. dist. mkd. T24S R8W S28 BT.
  - A Fir 16" dia., bears S.35°W., 50 lks. dist. mkd. T24S R8W S29 BT.
  - A Fir 24" dia., bears N.5½°W., 38 lks. dist. mkd. T24S R8W S20 BT.

BLM resurvey by C. Albert White;, Cadastral Surveyor and Donald R. Beck, Surveying Technician - under Group #427, Surveyed July/Aug. 1962 - (DCSO records Vol. 32 Page(s) 13326)

- 
- The Sec. cor., determined at record bearing and distance from the original bearing trees:
- A Fir 30" dia., bears N.40°E., 84 lks. dist. mkd. with a healed blaze and cruiser marks. Reblaze and mark "TR24S R8W S21 BT"
  - A Fir 20" dia., bears S.22¼°E., 19 lks. dist., mkd. with a healed blaze and cruiser marks. Reblaze and mark "T24S R8W S28 BT"
  - A Fir 27" dia., bears S.35°W., 50 lks. dist. mkd. with a healed blaze and old axe marks. Reblaze and mark "T24S R8W S29 BT"
  - A Fir 32" dia., bears N.5½°W., 38 lks. dist. mkd. with old axe marks, a healed blaze, and cruiser marks. Reblaze and mark "T24S R8W S20 BT"

At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 22" in the ground, with brass cap mkd:

T 24 S R 8 W  
S 20 S 21  
S 29 S 28  
1962