

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 20 and 21

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3357)

Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on W. face, from which
A Fir 20" dia., bears S.53°E., 139 lks. dist. mkd. ¼ S BT
A Fir 24" dia., bears N.23°W., 49 lks. dist. mkd. ¼ S BT.

BLM resurvey by C. Albert White;, Cadastral Surveyor and Donald R. Beck, Surveying Technician - under Group #427, Surveyed July/Aug. 1962 - (DCSO records Vol. 32 Page(s) 13328)

The ¼ sec. cor., determined from the remains of the original bearing trees and at the N. end of the original blazed line extending S., from which the original bearing trees:

- A downed Fir 35" dia., bears S.53°E., 119 lks. dist., no marks visible. (Rec. dist. 139 lks.)
- A Fir 40" dia., bears N.23°W., 49 lks. dist., no marks visible.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼
S 20 S 21
T 24 S R 8 W
1962

from which new bearing trees:

- A Fir 18" dia., bears S.18°E., 59 lks. dist. mkd. ¼ S21 BT
- A Fir 18" dia., bears S.77°W., 61 lks. dist. mkd. ¼ S20 BT