

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3358)

Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 16, 17, 20 and 21, marked T24S S16 on NE.; R8W S21 on SE.; S20 on SW.; and S17 on NW. faces, with 3 notches on S. and 4 notches on E. edges, from which

- A Fir 12" dia., bears N.27½°E., 57 lks. dist. mkd. T24S R8W S16 BT.
- A Fir 10" dia., bears S.4°E., 27 lks. dist. mkd. T24S R8W S21 BT.
- A Fir 14" dia., bears S.68°W., 54 lks. dist. mkd. T24S R8W S20 BT.
- A Fir 30" dia., bears N.29°W., 48 lks. dist. mkd. T24S R8W S17 BT.

BLM resurvey by C. Albert White;, Cadastral Surveyor and Donald R. Beck, Surveying Technician - under Group #427, Surveyed July/Aug. 1962 - (DCSO records Vol. 32 Page(s) 13328-29)

The Sec. cor., determined at record bearing and distance from the remaining original bearing trees:

- A Fir 25" dia., bears N.27½°E., 57 lks. dist., mkd. with a healed blaze and cruiser marks. Reblaze and mark "T24S R8W S16 BT"
- A Fir 22" dia., bears S.4°E., 27 lks. dist. mkd. with a healed blaze and cruiser marks. Reblaze and mark T24S R8W S21 BT.

A rotted Fir stump 15" dia., bears S.68°W., 54 lks. dist. At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 24	S R 8 W
S 17	S 16
S 20	S 21
1962	

from which new bearing trees

- A Fir 10" dia., bears S.42°W., 36 lks. dist. mkd. T24S R8W S20 BT.
- A Fir 15" dia., bears N.86°W., 81 lks. dist. mkd. T24S R8W S17 BT.

Fd BC & 4 BTS - Donald Peel, 4/1967 - C.S. File 55/30-2

(Cont. Next Page)

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 16, 17, 20 and 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Survey by Mark Smalley - For: Kenneth Ford - Jan. 1996 -
M 123-38

Corner Report

Found - 1962 Cadastral brass cap/iron pipe.
24" Fir N.86°W., 53.5 ft., healed.
26" Fir N.27½°E., 37.6 ft., healed, orig. BT.
30" Fir S.4°E., 17.8 ft., healed, orig. BT.
16" Fir S.42°W., 23.8 ft., healed.