

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 300440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 16 and 17

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3359)

Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on W. face, from which
A Fir 10" dia., bears N.77°E., 20 lks. dist. mkd. ¼ S BT
A Fir 10" dia., bears N.23°W., 7 lks. dist. mkd. ¼ S BT.

Survey by Mark Smalley - For: Kenneth Ford - Jan. 1996 - M 123-38

Set 5/8" x 48" Iron rod with alum. cap mkd. "LS 2354", from which new BTs:
16" Fir N.22°W., 10.5 ft. scribed ¼ S17 BT.
17" Fir N.40°W., 19.2 ft. scribed ¼ S17 BT.
17" Fir N.32°E., 19.7 ft. scribed ¼ S16 BT.
22" Fir S.64°W., 10.7 ft. scribed ¼ S17 BT.