

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_  
 Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3360)

-----  
 Set a post 4 ft. long, 4" sq., 24" in the ground for cor. to secs. 8, 9, 16 and 17 marked ,T24S S9 on NE.; R8W S16 on SE.; S17 on SW.; and S8 on NW. faces, with 4 notches on S. and E. edges, from which  
     A Fir 24" dia., bears N.52°E., 31 lks. dist. mkd. T24S R8W S9 BT.  
     A Fir 22" dia., bears S.18½°E., 34 lks. dist.mkd. T24S R8W S16 BT.  
     A Fir 24" dia., bears S.57°W., 10 lks. dist. mkd. T24S R8W S17 BT.  
     A Fir 15" dia., bears N.31°W., 9 lks. dist. mkd. T24S R8W S8 BT.

BLM corner remonumentation by Harold D. Corbin, Cadastral Surveyor, under Group #'s 350 and 427, Surveyed June 1959 - (DCSO records Vol. 30 Page(s) 12615)

-----  
 The sec. cor. determined at record bearing and distance from the remains of the original bearing trees:  
     A stump hole with roots of a Fir tree, bears N.52°E., 31 lks. dist.  
     A Fir snag 28" dia., bears S.18½°E., 34 lks. dist. with a healed blaze.  
     A Fir 37" dia., bears S.57°W., 10 lks. dist. with a healed blaze.  
     A rotted Fir stump bears N.31°W., 9 lks. dist.

At the corner point  
 Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 24	S R 8 W
S 8	S 9
S 17	S 16
1959	

from which  
     A Fir 20" dia., bears N.25°E., 54 lks. dist. mkd. T24S R8W S9 BT.  
     A Fir 42" dia., bears S.7°E., 185 lks. dist. mkd. T24S R8W S16 BT.  
     A Fir 34" dia., bears S.69½°W., 185 lks. dist. mkd. T24S R8W S17 BT.  
     A Fir 24" dia., bears N.29°W., 36 lks. dist. mkd. T24S R8w S8 BT.

(Cont. Next Page)

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 300500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 8, 9, 16 and 17

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Fd BC & 6 BTS - Donald Peel, 4/1967 - C.S. File 55/30-2

Mark Smalley for Kenneth Ford, Jan. 1996 - M123-38

- 
- |         |   |  |
|---------|---|--|
| Found   | - | 1959 Cadastral B.C.I.P.                      |
|         | - | 28" Fir, N.25°E., 35.6 ft. (healed)          |
|         | - | 34" Fir, S.7°E., 122.1 ft. (snag)            |
|         | - | 26" Fir, S.18½°E., 22.4 ft. (snag, orig. BT) |
|         | - | 50" Fir, S.57°W., 6.6 ft. (healed, orig. BT) |
| New BTs | - | 5" Fir, N.49°E., 8.4 ft. scribed "S 9 BT"    |
|         | - | 13" Fir, S.7°W., 47.0 ft. scribed "S 17 BT"  |