

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 8 and 9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3362)

-----  
Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on W. face, from which  
A Hemlock 10" dia., bears N.51°E., 9 lks. dist. mkd. ¼ S BT.  
A Fir 18" dia., bears S.41°W., 25 lks. dist. mkd. ¼ S BT.

Survey by Nick Juliano - For: Weyerhaeuser Co. - Sept. 1969  
C.S. File 55/120 and M 38-47

-----  
Found - Corner post gone.  
18" Hemlock, dozed out, scar visible.  
22" Fir, dozed out by cat, scar visible.  
(¼ corner reset by Weyerhaeuser from road location notes.)  
Set 2" Iron pipe with brass cap.  
Referenced with "W" nails and plates:  
32" Fir stump S.45°E., 31.7 ft.  
74" Fir stump North, 52.3 ft.