

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 33 only

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by - William H. Byars, Deputy Surveyor, Under Contract No. 292, dated Aug. 7, 1878 - (DCSO records Vol. 8 Page(s) 3295-96)

-----  
Set Dogwood post 40" long, 5" dia., 20" in ground for the qr. sec. cor. on South bdy. of sec. 33, from which  
A Hemlock 6" dia., bears S.40°W., 14 lks. dist.  
A Hemlock 24" dia., bears N.40°W., 31 lks. dist.

Fd. and used in GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3303-04)

GLO survey by Morris Wygant, compassman for Zachariah M. Derrick, U.S. Deputy Surveyor, under Contract #779, dated Feb. 7, 1908 - (DCSO records Vol. 8 Page(s) 3384)

-----  
No trace of old ¼ sec. cor. to be found after diligent search of old survey line.

BLM resurvey by C. Albert White;, Cadastral Surveyor and Donald R. Beck, Surveying Technician - under Group #427, Surveyed July/Aug. 1962 - (DCSO records Vol. 32 Page(s) 13319)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 18" in the ground, to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap mkd:

T 24 S R 8 W

¼ S 33

1962

from which

A Fir 20" dia., bears N.50°E., 133 lks. dist. mkd. ¼ S33 BT.

A Hemlock 11" dia., bears N.56°W., 58 lks. dist. mkd. ¼ S33 BT.

The fork of a Maple 13" dia., bears N.9°W., 63 lks. dist. mkd. ¼ S33 BT.