

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 340200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 28 and 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCSO records Vol. 8 Page(s) 3354)

Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on N. face, from which
A Cedar 12" dia., bears S.59°E., 79 lks. dist. mkd. ¼ S BT
A Cedar 20" dia., bears N.47°E., 29 lks. dist. mkd. ¼ S BT

BLM resurvey by C. Albert White;, Cadastral Surveyor and Donald R. Beck, Surveying Technician - under Group #427, Surveyed July/Aug. 1962 - (DCSO records Vol. 32 Page(s) 13325)

The ¼ sec. cor., determined at record bearing and distance from the remaining original bearing tree:

A Cedar 22" dia., bears N.47°E., 29 lks. dist., mkd. with open face and old axe marks. Reblaze and mark "¼ S28 BT"

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼ S 28
S 33

T 24 S R 8 W
1962

from which a new bearing tree

A Cedar 18" dia., bears S.7½°E., 72 lks. dist. mkd. ¼ S33 BT.