

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #619, dated June 5, 1893 - (DCS0 records Vol. 8 Page(s) 3356)

-----  
Set a post 3½ ft. long, 3" sq., 24" in the ground, for ¼ sec. cor. marked ¼ S on N. face, from which  
A Fir 18" dia., bears N.63°W., 65 lks. dist. mkd. ¼ S BT  
A Fir 30" dia., bears S.39½°E., 90 lks. dist. mkd. ¼ S BT.

BLM resurvey by C. Albert White;, Cadastral Surveyor and Donald R. Beck, Surveying Technician - under Group #427, Surveyed July/Aug. 1962 - (DCS0 records Vol. 32 Page(s) 13327)

-----  
The ¼ sec. cor., determined at record bearing and distance from the original bearing trees:

A stump hole bears N.63°W., 65 lks. dist.  
A Fir 40" dia., bears S.39½°E., 90 lks. dist. mkd. with a healed blaze and cruiser marks.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 21" in the ground, with brass cap mkd:

¼  $\frac{S\ 21}{S\ 28}$   
T 24 S R 8 W  
1962

from which new bearing trees

A Fir 20" dia., bears N.72½°W., 44 lks. dist. mkd. ¼ S21 BT.  
A Fir 11" dia., bears S.6°W., 69 lks. dist. mkd. ¼ S28 BT.

Douglas Co. Surveyor's Office - Crew: Stephen J. Flause and Jeff Lorsung - 3/12/2026 - C.S. File 67/62-21

-----  
Found - 3¼" BLM brass cap proj. 5".  
49" D. Fir S.40½°E. 60.2 ft. (Rec. S.39½°E. 90 lks) healed blaze, cruiser marks. Add 3½" mag nail right side center.  
Broken off 44" x 12 ft. D. fir snag N.72½°W. 29.0ft. Fully healed single blaze.  
22" G. Fir fallen out of position. Fully healed single blaze. Root hole near here. S.6°W. 45.3 ft.  
New - 13" G. Fir N.42°E. 22.6 ft. scribed "¼ S21 BT" on double blaze. 3½" mag nail right side center.  
10" G. Fir N.34°W. 13.3 ft. scribed "¼ S21 BT" on double blaze. 3½" mag nail right side center.  
Notes - Mon. on relative flat ground in mixed second growth approx 70 ft. south of gravel road.  
Continued next page

TOWNSHIP 24 RANGE 08 POINT IDENTIFIER # 340300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 28

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Alias \_\_\_\_\_ Description \_\_\_\_\_

Compass decl.  $14\frac{1}{4}^{\circ}\text{E}$ .  
TRIMBLE GEO XT POSITION  
 $43^{\circ}.41188671$  N.  $123^{\circ}.65377514$  W.